




SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.15mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TS-1010B-X-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	H: 3.5
Position Foot	A: With B: without

⑤	Terminal	—	2	Brass (0.30t)	ag Plated	—
④	Contact	—	2	F.ag/SUS		—
③	Base	—	1	LCP	Natural	—
②	Cover	—	1	Brass	Tin plated	—
①	Keystake	—	1	LCP		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

						DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
						DWN		DATE		VIEW:	PART NO.:		
						CHKD		DATE		UNIT: mm	DWG NO.:		
						APPD		DATE		SIZE: A4	TS-1010B-X-X		
REVISIONS						UNSPECIFIED TOLERANCES					WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn						XKB INDUSTRIAL PRECISION CO.,LIMITED					1.0g	1/1	A0
△X						units: mm							
△X						tolerance: X.X ±0.2mm							
△X						X.XX ±0.1mm							
MARK	DESCRIPTION	DATE	REVISED	APPROVED		X.XXX ±0.05mm							